

RO System's time has gone,  
now time to take TODI...




# todi<sup>®</sup> - Plus



## SPECIFICATION

MODEL	ORG TODI PLUS
Purification Capacity	15 Liter/Hour
Operating Voltage	240 Volt Ac, 50 Hz
Duty Cycle	75 Liters/Day (Max)
System Wattage	50 watts
Storage Capacity	8 Liters
Inlet Water Pressure	0.3(min)-2.2(max) kg/cm2
Booster Pump	24 V DC- 100 GPD
RO Membrane	2012 – 100 GPD
UV Lamp	11 Watt
UF Membrane	0.1 Micron
UV Circulating Pump	24 V DC / 300 GPD
Alkaline cartridge	–
Dispensing Pump	–
Digital Dispensing Switch	–
Micro Controller Board	2 Unit (Main + Auxiliary)
Solenoid Valve	24 V DC, 2 Nos
TDS Display	0 to 999 ppm
Service Hour Display	0 to 200 Hrs
BodyMaterial & FP.Colour	ABS, Food Grade, Blue
Dimension (in mm)	L410 X W385 X H465
Gross Weight	11.05 Kg
Net Weight	9.55 Kg


## UNIQUE FEATURES



TDS of Purified Water Display



Remaining Service Hour Display



UV Sterilization at Regular Interval

### FEATURES FOR ORG TODI - PLUS

- Suitable for all type of supply water like borewell, tanker or municipal water.
- TDS of purified water can be set digitally by Users.
- It can be used in Low TDS as well as High TDS of raw water.
- TDS of purified water display on front panel.
- User gets accuracy of purified water till  $\pm 10$  ppm TDS.
- LED Indication for purification process i.e. RO/UV/UF on front panel.
- Indication for storage tank full and low pressure on front panel.
- TODI Technology gives low rejection water.
- Change of raw water TDS doesn't affect the TDS of purified water.

**ORG ENGITECH LIMITED**

+91 90999 03226 | info@orgengitech.com | www.orgwater.com