

RO System's time has gone,  
now time to take TODI...




# todi<sup>®</sup> - Alkalinator<sup>™</sup>



## SPECIFICATION

MODEL	ORG TODI Alkalinator
Purification Capacity	15 Liter/Hour
Operating Voltage	240 Volt Ac, 50 Hz
Duty Cycle	75 Liters/Day (Max)
System Wattage	50 watts
Storage Capacity	8 Liters
Inlet Water Pressure	0.3(min)-2.2(max) kg/cm <sup>2</sup>
Booster Pump	Double Head-100 GPD
RO Membrane	2012 – 100 GPD
UV Lamp	–
UF Membrane	0.1 Micron
UV Circulating Pump	–
Alkaline cartridge	Anti-oxident Alkaline Mineral Ball
Dispensing Pump	24 V DC / 300 GPD
Digital Dispensing Switch	2 Nos. (Purified & Alkaline )
Micro Controller Board	3 Unit (Main + Auxiliary)
Solenoid Valve	24 V DC, 4 Nos
TDS Display	0 to 999 ppm
Service Hour Display	0 to 200 Hrs
BodyMaterial & FP.Colour	ABS, F. Grade, Burgundy
Dimension (in mm)	L410 X W385 X H465
Gross Weight	11.45 Kg
Net Weight	9.95 Kg


## UNIQUE FEATURES



TDS of Purified Water Display



Remaining Service Hour Display



Dual digital dispensing purified / Alkaline water



Live anti-oxidant alkaline hydrogen reach water

## FEATURES FOR ORG TODI - ALKLINATOR

- Suitable for all type of supply water like borewell, tanker or municipal water.
- TDS of purified water can be set digitally by Users.
- It can be used in Low TDS as well as High TDS of raw water.
- TDS of purified water display on front panel.
- User gets accuracy of purified water till  $\pm 10$  ppm TDS.
- LED Indication for purification process i.e. RO/UV/UF on front panel.
- Indication for storage tank full and low pressure on front panel.
- TODI Technology gives low rejection water.
- Change of raw water TDS doesn't affect the TDS of purified water.

**ORG ENGITECH LIMITED**

+91 90999 03226 | info@orgengitech.com | www.orgwater.com